GSB Chemical Co.

Chemwatch: 21-9712 Version No: 4.1.1.1 Safety Data Sheet according to WHS and ADG requirements Chemwatch Hazard Alert Code: 1

Issue Date: 12/07/2014 Print Date: 09/11/2015 Initial Date: Not Available S.GHS.AUS.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product name	124C Ultrasonic Cleaning Solution	
Synonyms	Mildly Alkaline Salts solution,	
Other means of identification	Not Available	
Relevant identified uses of the substance or mixture and uses advised against		

Details of the supplier of the safety data sheet

Registered company name	GSB Chemical Co.
Address	84 Camp Road Broadmeadows 3047 VIC Australia
Telephone	+61 3 9457 1125 (8am-5pm, Monday - Friday)
Fax	+61 3 9459 7978
Website	Not Available
Email	info@gsbchem.com.au

Emergency telephone number

Association / Organisation	Not Available
Emergency telephone numbers	+61 3 9457 1125 (8am-5pm, Monday - Friday)
Other emergency telephone numbers	13 11 26 (After hours)

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

NON-HAZARDOUS CHEMICAL. NON-DANGEROUS GOODS. According to the Model WHS Regulations and the ADG Code.

Poisons Schedule	\$5				
GHS Classification [1]	Chronic Aquatic Hazard Category 4				
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HSIS ; 3. Classification drawn from EC Directive 1272/2008 - Annex VI				
Label elements					
GHS label elements	Not Applicable				
SIGNAL WORD	NOT APPLICABLE				
Hazard statement(s)					
H413	May cause long lasting harmful effects to aquatic life				
Precautionary statement(s)) Prevention				
P273	Avoid release to the environment.				
Precautionary statement(s) Not Applicable) Response				
Precautionary statement(s)) Storage				
Not Applicable					
Precautionary statement(s)) Disposal				
P501	Dispose of contents/container in accordance with local regulations.				

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
7758-29-4	<10	sodium tripolyphosphate
Not Available	balance	ingredients at levels determined not to be hazardous
7732-18-5	60-100	water

SECTION 4 FIRST AID MEASURES

Description of first aid measures

Eye Contact	 If this product comes in contact with the eyes: Wash out immediately with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Seek medical attention without delay; if pain persists or recurs seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	 If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary.
Ingestion	 If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Seek medical advice.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

- There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

Special hazards arising from the substrate or mixture

Fire Incompatibility None known.

Advice for firefighters	
Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves in the event of a fire. Prevent, by any means available, spillage from entering drains or water courses. Use fire fighting procedures suitable for surrounding area. DO NOT approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire. Equipment should be thoroughly decontaminated after use.
Fire/Explosion Hazard	 Non combustible. Not considered a significant fire risk, however containers may burn. Decomposition may produce toxic fumes of; phosphorus oxides (POx)May emit poisonous fumes.May emit corrosive fumes.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Minor Spills	 Environmental hazard - contain spillage. Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment. Contain and absorb spill with sand, earth, inert material or vermiculite. Wipe up. Place in a suitable, labelled container for waste disposal.
Major Spills	 Environmental hazard - contain spillage. Moderate hazard. Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water course.

	 Stop leak if safe to do so. Contain spill with sand, earth or vermiculite. Collect recoverable product into labelled containers for recycling. Neutralise/decontaminate residue (see Section 13 for specific agent). Collect solid residues and seal in labelled drums for disposal. Wash area and prevent runoff into drains. After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using. If contamination of drains or waterways occurs, advise emergency services.
Personal Protective Equipment a	dvice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

	 DO NOT allow clothing wet with material to stay in contact with skin Avoid all personal contact, including inhalation.
	 Wear protective clothing when risk of exposure occurs.
	► Use in a well-ventilated area.
	Prevent concentration in hollows and sumps.
	DO NOT enter confined spaces until atmosphere has been checked.
	DO NOT allow material to contact humans, exposed food or food utensils.
Safe handling	Avoid contact with incompatible materials.
Gare mananing	When handling, DO NOT eat, drink or smoke.
	Keep containers securely sealed when not in use.
	Avoid physical damage to containers.
	Always wash hands with soap and water after handling.
	 Work clothes should be laundered separately. Launder contaminated clothing before re-use.
	Use good occupational work practice.
	Observe manufacturer's storage and handling recommendations contained within this SDS.
	Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.
	► Store in original containers.
	 Keep containers securely sealed.
Other information	Store in a cool, dry, well-ventilated area.
Other Information	Store away from incompatible materials and foodstuff containers.
	 Protect containers against physical damage and check regularly for leaks.
	Observe manufacturer's storage and handling recommendations contained within this SDS.

Conditions for safe storage, including any incompatibilities

Suitable container	 Polyethylene or polypropylene container. Packing as recommended by manufacturer. Check all containers are clearly labelled and free from leaks.
Storage incompatibility	 Phosphates are incompatible with oxidising and reducing agents. Phosphates are susceptible to formation of highly toxic and flammable phosphine gas in the presence of strong reducing agents such as hydrides. Partial oxidation of phosphates by oxidizing agents may result in the release of toxic phosphorus oxides.

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Not Available

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1		TEEL-2	TEEL-3
sodium tripolyphosphate	Sodium tripolyphosphate 0.22 mg/m3			2.5 mg/m3	620 mg/m3
Ingredient	Original IDLH		Revised IDLH		
sodium tripolyphosphate	Not Available		Not Available		
ingredients at levels determined not to be hazardous	Not Available		Not Available		
water	Not Available		Not Available		

Exposure controls

Appropriate engineering	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.
controls	Employers may need to use multiple types of controls to prevent employee overexposure.
	General exhaust is adequate under normal operating conditions. Local exhaust ventilation may be required in special circumstances. If risk of overexposure exists, wear approved respirator. Supplied-air type respirator may be required in special circumstances. Correct fit is essential to ensure adequate protection. Provide adequate ventilation in warehouses and enclosed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

	Type of Contaminant:		Air Speed:
	solvent, vapours, degreasing etc., evaporating from tank (in still air).		0.25-0.5 m/s (50-100 f/min)
	aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfer acid fumes, pickling (released at low velocity into zone of active generation)	s, welding, spray drift, plating	0.5-1 m/s (100-200 f/min.)
	direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas dis zone of rapid air motion)	scharge (active generation into	1-2.5 m/s (200-500 f/min.)
	grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial ve air motion)	locity into zone of very high rapid	2.5-10 m/s (500-2000 f/min.)
	Within each range the appropriate value depends on:		
	Lower end of the range	Upper end of the range	
	1: Room air currents minimal or favourable to capture	1: Disturbing room air currents	
	2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity	
	3: Intermittent, low production.	3: High production, heavy use	
	4: Large hood or large air mass in motion	4: Small hood-local control only	
	Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple ext of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point distance from the contaminating source. The air velocity at the extraction fan, for example, should be solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerati apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when	should be adjusted, accordingly, a a minimum of 1-2 m/s (200-400 f/m ons, producing performance deficit	fter reference to hin) for extraction of s within the extraction
Personal protection			
	 Cofety alegenes with side shields 		
Eye and face protection	 Safety glasses with side shields. Chemical goggles. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irrit lenses or restrictions on use, should be created for each workplace or task. This should include chemicals in use and an account of injury experience. Medical and first-aid personnel should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove at the first signs of eye redness or irritation - lens should be removed in a clean environment only Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent] 	a review of lens absorption and ad trained in their removal and suitab contact lens as soon as practicabl	sorption for the class of le equipment should be e. Lens should be remo
Eye and face protection Skin protection	 Chemical goggles. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irrit lenses or restrictions on use, should be created for each workplace or task. This should include chemicals in use and an account of injury experience. Medical and first-aid personnel should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove at the first signs of eye redness or irritation - lens should be removed in a clean environment only 	a review of lens absorption and ad trained in their removal and suitab contact lens as soon as practicabl	sorption for the class of le equipment should b e. Lens should be rem
	 Chemical goggles. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irrit lenses or restrictions on use, should be created for each workplace or task. This should include chemicals in use and an account of injury experience. Medical and first-aid personnel should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove at the first signs of eye redness or irritation - lens should be removed in a clean environment only Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent] 	a review of lens absorption and ad trained in their removal and suitab contact lens as soon as practicabl r after workers have washed hands ality which vary from manufacturer alculated in advance and has there ve gloves and has to be observed ve ves include: hal equivalent). In higher (breakthrough time greated time greater than 60 minutes accord when considering gloves for long-ter	Isorption for the class of le equipment should be e. Lens should be rem a thoroughly. [CDC NIC to manufacturer. When fore to be checked prior when making a final er than 240 minutes bording to EN 374, AS/N erm use.
Skin protection	 Chemical goggles. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irrit lenses or restrictions on use, should be created for each workplace or task. This should include chemicals in use and an account of injury experience. Medical and first-aight personnel should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove at the first signs of eye redness or irritation - lens should be removed in a clean environment only Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent] See Hand protection below Wear chemical protective gloves, e.g. PVC. Wear safety footwear or safety gumboots, e.g. Rubber The selection of suitable gloves does not only depend on the material, but also on further marks of qu the chemical is a preparation of several substances, the resistance of the glove material can not be c to the application. The exact break through time for substances has to be obtained from the manufacturer of the protectin choice. Suitability and durability of glove type is dependent on usage. Important factors in the selection of glo frequency and duration of contact, chemical resistance of glove material, glove thickness and dexterity Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or nation 4 worken only brief contact is expected, a glove with a protection class of 5 or according to EN 374, AS/NZS 2161.1.0 r national equivalent) is recommended. When only brief contact is expected, a glove with a protection class of 5 or according to EN 374, AS/NZS 2161.1.0 r national equivalent) is recommended. Some glove polymer types are less affected by movement and this should be taken into account to Contarninated gloves should be replaced. Gloves must only be worn on clean hands. After	a review of lens absorption and ad trained in their removal and suitab contact lens as soon as practicabl r after workers have washed hands ality which vary from manufacturer alculated in advance and has there ve gloves and has to be observed ve ves include: hal equivalent). In higher (breakthrough time greated time greater than 60 minutes accord when considering gloves for long-ter	Isorption for the class of le equipment should be e. Lens should be rem a thoroughly. [CDC NIC to manufacturer. When fore to be checked prior when making a final er than 240 minutes bording to EN 374, AS/N erm use.
Skin protection Hands/feet protection	 Chemical goggles. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irrit lenses or restrictions on use, should be created for each workplace or task. This should include chemicals in use and an account of injury experience. Medical and first-aign personnel should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove at the first signs of eye redness or irritation - lens should be removed in a clean environment only Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent] See Hand protection below Wear chemical protective gloves, e.g. PVC. Wear safety footwear or safety gumboots, e.g. Rubber The selection of suitable gloves does not only depend on the material, but also on further marks of qu the chemical is a preparation of several substances, the resistance of the glove material can not be c to the application. The exact break through time for substances has to be obtained from the manufacturer of the protectin choice. Suitability and durability of glove type is dependent on usage. Important factors in the selection of glove frequency and duration of contact, chemical resistance of glove material, glove thickness and dexterity Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent) is recommended. When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended. Some glove polymer types are less affected by movement and this should be taken into account b. Contaminated gloves should be replaced. Gloves must only be wom on clean hands. After using gloves, hands should be washed and dried thor recommended. 	a review of lens absorption and ad trained in their removal and suitab contact lens as soon as practicabl r after workers have washed hands ality which vary from manufacturer alculated in advance and has there ve gloves and has to be observed ve ves include: hal equivalent). In higher (breakthrough time greated time greater than 60 minutes accord when considering gloves for long-ter	Isorption for the class of le equipment should be e. Lens should be reme to manufacturer. Whe fore to be checked pri- vhen making a final er than 240 minutes bording to EN 374, AS/ erm use.

Respiratory protection

Not Available

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance Yellow liquid with a characteristic odour; miscible with water.

Physical state	#00Liquid	Relative density (Water = 1)	1.1

Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Applicable
pH (as supplied)	9	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	100	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Applicable	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Applicable	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Applicable	Volatile Component (%vol)	>90
Vapour pressure (kPa)	4.4 @20C	Gas group	Not Available
Solubility in water (g/L)	#01miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

ingredients at levels determined not to be hazardous water	TOXICITY Not Available TOXICITY Oral (rat) LD50: >90000 mg/kg ^[2]	IRRITATION Not Available IRRITATION Not Available		
sodium tripolyphosphate	TOXICITY Dermal (rabbit) LD50: >3160 mg/kg* ^[2] Oral (rat) LD50: >2000 mg/kg ^[1]	IRRITATION Not Available		
124C Ultrasonic Cleaning Solution	TOXICITY Not Available	IRRITATION Not Available		
Chronic	Substance accumulation, in the human body, may occur and m Sodium phosphate dibasic can cause stones in the kidney, loss	,		
Eye	There is some evidence to suggest that this material can cause eye irritation and damage in some persons.		e persons.	
Ingestion Skin Contact	pressure, slow pulse, cyanosis, spasms of the wrist, coma and There is some evidence to suggest that this material can caus	As absorption of phosphates from the bowel is poor, poisoning this way is less likely. Effects can include vomiting, tiredness, fever, diarrhoea, low blood ressure, slow pulse, cyanosis, spasms of the wrist, coma and severe body spasms. There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons. Doen cuts, abraded or initiated skin should not be exposed to this material		
Inhaled	There is some evidence to suggest that the material can cause respiratory irritation in some persons. The body's response to such irritation can cause further ung damage. Not normally a hazard due to non-volatile nature of product			

Respiratory or Skin \odot STOT - Repeated Exposure \odot sensitisation Mutagenicity \odot Aspiration Hazard 0 X - Data available but does not fill the criteria for classification Legend: Data required to make classification available

O – Data Not Available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

Ingredient	Endpoint	Test Duration	Species	Value	Source
sodium tripolyphosphate	EC50	48	Crustacea	>70.7<101.3mg/L	2
sodium tripolyphosphate	EC50	96	Algae or other aquatic plants	69.20mg/L	2
water	LC50	96	Fish	897.5200mg/L	3
water	EC50	96	Algae or other aquatic plants	8768.8740mg/L	3

On the basis of available evidence concerning either toxicity, persistence, potential to accumulate and or observed environmental fate and behaviour, the material may present a danger, immediate or long-term and /or delayed, to the structure and/ or functioning of natural ecosystems.

May cause long-term adverse effects in the aquatic environment.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

For Phosphate: The principal problems of phosphate contamination of the environment relates to eutrophication processes in lakes and ponds. Phosphorus is an essential plant nutrient and is usually the limiting nutrient for blue-green algae.

Aquatic Fate: Lakes overloaded with phosphates is the primary catalyst for the rapid growth of algae in surface waters. Planktonic algae cause turbidity and flotation films. Shore algae cause ugly muddying, films and damage to reeds. Decay of these algae causes oxygen depletion in the deep water and shallow water near the shore. The process is self-perpetuating because an anoxic condition at the sediment/water interface causes the release of more adsorbed phosphates from the sediment. The growth of algae produces undesirable effects on the treatment of water for drinking purposes, on fisheries, and on the use of lakes for recreational purposes.

DO NOT discharge into sewer or waterway

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
water	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation
water	LOW (LogKOW = -1.38)

Mobility in soil

Ingredient	Mobility
water	LOW (KOC = 14.3)

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked. A Hierarchy of Controls seems to be common - the user should investigate: Reduction Reuse Recycling Disposal (if all else fails)
Product / Packaging disposal This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate. • DO NOT allow wash water from cleaning or process equipment to enter drains. • It may be necessary to collect all wash water for treatment before disposal. • In all cases disposal to sever may be subject to local laws and regulations and these should be considered first. • Where in doubt contact the responsible authority. • Recycle wherever possible. • Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified. • Dispose of by: burial in a land-fill specifically licenced to accept chemical and / or pharmaceutical wastes or incineration in a licenced apparatus (after admixture with suitable combustible material). • Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.

SECTION 14 TRANSPORT INFORMATION

Labels Required

Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

SODIUM TRIPOLYPHOSPHATE(7758-29-4) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Inventory of Chemical Substances (AICS)

Not Applicable

WATER(7732-18-5) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Inventory of Chemical Substances (AICS)

National Inventory	Status
Australia - AICS	Y
Canada - DSL	Y
Canada - NDSL	N (sodium tripolyphosphate; water)
China - IECSC	Y
Europe - EINEC / ELINCS / NLP	Y
Japan - ENCS	N (water)
Korea - KECI	Y
New Zealand - NZIoC	Y
Philippines - PICCS	Y
USA - TSCA	Y
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 OTHER INFORMATION

Other information

Ingredients with multiple cas numbers

Name	CAS No
sodium tripolyphosphate	15091-98-2, 7758-29-4

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at: www.chemwatch.net

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

- PC TWA: Permissible Concentration-Time Weighted Average PC STEL: Permissible Concentration-Short Term Exposure Limit
- IARC: International Agency for Research on Cancer
- ACGIH: American Conference of Governmental Industrial Hygienists
- STEL: Short Term Exposure Limit TEEL: Temporary Emergency Exposure Limit。
- IDLH: Immediately Dangerous to Life or Health Concentrations
- OSF: Odour Safety Factor
- NOAEL :No Observed Adverse Effect Level
- LOAEL: Lowest Observed Adverse Effect Level
- TLV: Threshold Limit Value
- LOD: Limit Of Detection
- OTV: Odour Threshold Value
- BCF: BioConcentration Factors
- BEI: Biological Exposure Index