

1098 HS Fount Solution

Chemwatch Material Safety Data Sheet
Issue Date: 10-Jul-2013
A317LP

Hazard Alert Code: MODERATE

CHEMWATCH 21-9552
Version No:3.1.1.1
Page 1 of 16

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

1098 HS Fount Solution

SYNONYMS

"Aqueous, electrolyte solution, fountain solution."

PRODUCT USE

Used according to manufacturer's directions.

Water treatment additive for lithographic printing. Applied via printing machinery.

SUPPLIER

Company: GSB Chemical Co. Pty Ltd

Address:

84 Camp Road

Broadmeadows

VIC, 3047

Australia

Telephone: +61 3 9457 1125

Fax: +61 3 9459 7978


Email: info@gsbchem.com.au

Section 2 - HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE

HAZARDOUS SUBSTANCE. NON-DANGEROUS GOODS. According to the Criteria of NOHSC, and the ADG Code.

CHEMWATCH HAZARD RATINGS



RISK

SAFETY

continued...

1098 HS Fount Solution

Hazard Alert Code: MODERATE

Chemwatch Material Safety Data Sheet

Issue Date: 10-Jul-2013

A317LP

CHEMWATCH 21-9552

Version No:3.1.1.1

Page 2 of 16

Section 2 - HAZARDS IDENTIFICATION

- Harmful by inhalation, in contact with skin and if swallowed.
 - Irritating to eyes, respiratory system and skin.
 - May cause SENSITISATION by skin contact.
 - Harmful to aquatic organisms, may cause long- term adverse effects in the aquatic environment.
 - May cause long- term adverse effects in the environment.
 - Cumulative effects may result following exposure*.
 - Vapours potentially cause drowsiness and dizziness*.
- * (limited evidence).
- Do not breathe gas/fumes/vapour/spray.
 - Avoid contact with skin.
 - Avoid contact with eyes.
 - Wear suitable protective clothing.
 - Wear suitable gloves.
 - Wear eye/face protection.
 - Use only in well ventilated areas.
 - Keep container in a well ventilated place.
 - To clean the floor and all objects contaminated by this material, use water.
 - Keep container tightly closed.
 - Keep away from food, drink and animal feeding stuffs.
 - In case of contact with eyes, rinse with plenty of water and contact Doctor or Poisons Information Centre.
 - If swallowed, IMMEDIATELY contact Doctor or Poisons Information Centre. (show this container or label).

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
D- glucose	50-99-7	<10
sodium phosphate	7632-05-5	<10
alkyl glycol ether surfactants		<10
5- chloro- 2- methyl- 4- isothiazolin- 3- one	26172-55-4	<10
corrosion inhibitors		<10
water	7732-18-5	>60

Section 4 - FIRST AID MEASURES

SWALLOWED

- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully.
- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
- Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
- Seek medical advice.

continued...

1098 HS Fount Solution

Hazard Alert Code: MODERATE

Chemwatch Material Safety Data Sheet

Issue Date: 10-Jul-2013

A317LP

CHEMWATCH 21-9552

Version No:3.1.1.1

Page 3 of 16

Section 4 - FIRST AID MEASURES

EYE

- If this product comes in contact with the eyes:
 - Wash out immediately with fresh running water.
 - Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
 - Seek medical attention without delay; if pain persists or recurs seek medical attention.
 - Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

- If skin contact occurs:
 - Immediately remove all contaminated clothing, including footwear.
 - Flush skin and hair with running water (and soap if available).
 - Seek medical attention in event of irritation.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
- Transport to hospital, or doctor.

NOTES TO PHYSICIAN

Treat symptomatically.

For acute or short term repeated exposures to ethanol:

- Acute ingestion in non-tolerant patients usually responds to supportive care with special attention to prevention of aspiration, replacement of fluid and correction of nutritional deficiencies (magnesium, thiamine pyridoxine, Vitamins C and K).
- Give 50% dextrose (50-100 ml) IV to obtunded patients following blood draw for glucose determination.
- Comatose patients should be treated with initial attention to airway, breathing, circulation and drugs of immediate importance (glucose, thiamine).
- Decontamination is probably unnecessary more than 1 hour after a single observed ingestion. Cathartics and charcoal may be given but are probably not effective in single ingestions.
- Fructose administration is contra-indicated due to side effects.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

■ The product contains a substantial proportion of water, therefore there are no restrictions on the type of extinguishing media which may be used. Choice of extinguishing media should take into account surrounding areas.

Though the material is non-combustible, evaporation of water from the mixture, caused by the heat of nearby fire, may produce floating layers of combustible substances.

In such an event consider:

- foam.
- dry chemical powder.
- carbon dioxide.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear full body protective clothing with breathing apparatus.

continued...

1098 HS Fount Solution

Hazard Alert Code: MODERATE

Chemwatch Material Safety Data Sheet

Issue Date: 10-Jul-2013

A317LP

CHEMWATCH 21-9552

Version No:3.1.1.1

Page 4 of 16

Section 5 - FIRE FIGHTING MEASURES

- Prevent, by any means available, spillage from entering drains or water course.
- Use water delivered as a fine spray to control fire and cool adjacent area.
- Avoid spraying water onto liquid pools.
- DO NOT approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.

FIRE/EXPLOSION HAZARD

- Combustible.
- Slight fire hazard when exposed to heat or flame.
- Heating may cause expansion or decomposition leading to violent rupture of containers.
- On combustion, may emit toxic fumes of carbon monoxide (CO).
- May emit acrid smoke.
- Mists containing combustible materials may be explosive.

Combustion products include: carbon dioxide (CO₂), phosphorus oxides (PO_x), other pyrolysis products typical of burning organic material.

May emit poisonous fumes.

FIRE INCOMPATIBILITY

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear full body protective clothing with breathing apparatus.
- Prevent, by any means available, spillage from entering drains or water course.
- Use fire fighting procedures suitable for surrounding area.
- Do not approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.
- Equipment should be thoroughly decontaminated after use.

HAZCHEM

None

Section 6 - ACCIDENTAL RELEASE MEASURES

MINOR SPILLS

Environmental hazard - contain spillage.

- Remove all ignition sources.
- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact with the substance, by using protective equipment.
- Contain and absorb spill with sand, earth, inert material or vermiculite.
- Wipe up.
- Place in a suitable, labelled container for waste disposal.

MAJOR SPILLS

Environmental hazard - contain spillage.

- Absorb or contain isothiazolinone liquid spills with sand, earth, inert material or vermiculite.
- The absorbent (and surface soil to a depth sufficient to remove all of the biocide) should be shovelled into a drum and treated with an 11% solution of sodium metabisulfite (Na₂S₂O₅) or sodium bisulfite (NaHSO₃), or 12% sodium sulfite (Na₂SO₃) and 8% hydrochloric acid (HCl).
- Glutathione has also been used to inactivate the isothiazolinones.
- Use 20 volumes of decontaminating solution for each volume of biocide, and let containers stand for at least 30 minutes to deactivate microbicide before disposal.

continued...

1098 HS Fount Solution

Hazard Alert Code: MODERATE

Chemwatch Material Safety Data Sheet
Issue Date: 10-Jul-2013
A317LP

CHEMWATCH 21-9552
Version No:3.1.1.1
Page 5 of 16

Section 6 - ACCIDENTAL RELEASE MEASURES

- If contamination of drains or waterways occurs, advise emergency services.
- After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- DO NOT allow clothing wet with material to stay in contact with skin.
- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.
- DO NOT enter confined spaces until atmosphere has been checked.
- DO NOT allow material to contact humans, exposed food or food utensils.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately. Launder contaminated clothing before re-use.
- Use good occupational work practice.
- Observe manufacturer's storage and handling recommendations contained within this MSDS.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

SUITABLE CONTAINER

- Metal can or drum
- Packaging as recommended by manufacturer.
- Check all containers are clearly labelled and free from leaks.

STORAGE INCOMPATIBILITY

- Avoid reaction with oxidising agents.

STORAGE REQUIREMENTS

- Store in original containers.
- Keep containers securely sealed.
- No smoking, naked lights or ignition sources.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storage and handling recommendations contained within this MSDS.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



+: May be stored together

continued...

1098 HS Fount Solution

Hazard Alert Code: MODERATE

Chemwatch Material Safety Data Sheet

Issue Date: 10-Jul-2013

A317LP

CHEMWATCH 21-9552

Version No:3.1.1.1

Page 6 of 16

Section 7 - HANDLING AND STORAGE

O: *May be stored together with specific preventions*

X: *Must not be stored together*

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

The following materials had no OELs on our records

- D- glucose: CAS:50- 99- 7 CAS:492- 62- 6 CAS:492- 61- 5
CAS:5996- 10- 1
- sodium phosphate: CAS:7632- 05- 5
- 5- chloro- 2- methyl- 4- isothiazolin- 3-
one: CAS:26172- 55- 4
- water: CAS:7732- 18- 5

MATERIAL DATA

1098 HS FOUNT SOLUTION:

5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE:

SODIUM PHOSPHATE:

Sensory irritants are chemicals that produce temporary and undesirable side-effects on the eyes, nose or throat. Historically occupational exposure standards for these irritants have been based on observation of workers' responses to various airborne concentrations. Present day expectations require that nearly every individual should be protected against even minor sensory irritation and exposure standards are established using uncertainty factors or safety factors of 5 to 10 or more. On occasion animal no-observable-effect-levels (NOEL) are used to determine these limits where human results are unavailable. An additional approach, typically used by the TLV committee (USA) in determining respiratory standards for this group of chemicals, has been to assign ceiling values (TLV C) to rapidly acting irritants and to assign short-term exposure limits (TLV STELs) when the weight of evidence from irritation, bioaccumulation and other endpoints combine to warrant such a limit. In contrast the MAK Commission (Germany) uses a five-category system based on intensive odour, local irritation, and elimination half-life. However this system is being replaced to be consistent with the European Union (EU) Scientific Committee for Occupational Exposure Limits (SCOEL); this is more closely allied to that of the USA.

OSHA (USA) concluded that exposure to sensory irritants can:

- cause inflammation
- cause increased susceptibility to other irritants and infectious agents
- lead to permanent injury or dysfunction
- permit greater absorption of hazardous substances and
- acclimate the worker to the irritant warning properties of these substances thus increasing the risk of overexposure.

1098 HS FOUNT SOLUTION:

5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE:

CEL TWA: 0.1 mg/m³; STEL 0.3 mg/m³ total isothiazolinones (Rohm and Haas)

(CEL = Chemwatch Exposure Limit).

D-GLUCOSE:

SODIUM PHOSPHATE:

It is the goal of the ACGIH (and other Agencies) to recommend TLVs (or their equivalent) for all substances for which there is evidence of health effects at airborne concentrations encountered in the workplace.

At this time no TLV has been established, even though this material may produce adverse health effects (as

continued...

1098 HS Fount Solution

Hazard Alert Code: MODERATE

Chemwatch Material Safety Data Sheet

Issue Date: 10-Jul-2013

A317LP

CHEMWATCH 21-9552

Version No:3.1.1.1

Page 7 of 16

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

evidenced in animal experiments or clinical experience). Airborne concentrations must be maintained as low as is practically possible and occupational exposure must be kept to a minimum.

NOTE: The ACGIH occupational exposure standard for Particles Not Otherwise Specified (P.N.O.S) does NOT apply.

1098 HS FOUNT SOLUTION:

For diethylene glycol monobutyl ether:

CEL TWA: 15.5 ppm, 100 mg/m³

(CEL = Chemwatch Exposure Limit)

In studies involving the inhalation toxicity of diethylene glycol monobutyl ether, exposure for 6 hours daily at 100 mg/m³ had no effect. This concentration is in the range of the saturated vapour concentration.

Local damage was produced following inhalation of concentrations higher than the saturated vapour concentrations, that is, during inhalation of the aerosol (350 mg/m³). Since the only potential effects of inhalation are restricted to local discomfort (in the aerosol concentration range) the substance is classified in category I for the limitation of exposure peaks.

Teratogenicity studies have not revealed prenatal toxic effects at high oral doses and this ether is classified in pregnancy risk group C.

For ethanol:

Odour Threshold Value: 49-716 ppm (detection), 101 ppm (recognition)

Eye and respiratory tract irritation do not appear to occur at exposure levels of less than 5000 ppm and the TLV-TWA is thought to provide an adequate margin of safety against such effects. Experiments in man show that inhalation of 1000 ppm caused slight symptoms of poisoning and 5000 ppm caused strong stupor and morbid sleepiness. Subjects exposed to 5000 ppm to 10000 ppm experienced smarting of the eyes and nose and coughing. Symptoms disappeared within minutes. Inhalation also causes local irritating effects to the eyes and upper respiratory tract, headaches, sensation of heat intraocular tension, stupor, fatigue and a need to sleep. At 15000 ppm there was continuous lachrymation and coughing.

The saturated vapour concentration of phosphoric acid exceeds the TLV. The TLV-TWA is based by analogy from comparable experience and data for sulfuric acid. Exposure at or below this limit is thought to prevent throat irritation amongst unacclimatised workers.

Fumes of phosphorus pentoxide at concentrations between 0.8 and 5.4 mg/m³ were reported to be noticeable but not uncomfortable whilst concentrations between 3.6 and 11.3 mg/m³ produced coughing in unacclimatised workers but were tolerable. Concentrations of 100 mg/m³ were unbearable except in inured workers.

WATER:

No exposure limits set by NOHSC or ACGIH.

PERSONAL PROTECTION



EYE

- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in

continued...

1098 HS Fount Solution

Hazard Alert Code: MODERATE

Chemwatch Material Safety Data Sheet

Issue Date: 10-Jul-2013

A317LP

CHEMWATCH 21-9552

Version No:3.1.1.1

Page 8 of 16

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent].

HANDS/FEET

- Wear chemical protective gloves, e.g. PVC.
- Wear safety footwear or safety gumboots, e.g. Rubber.

NOTE:

- The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.
- Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and

has to be observed when making a final choice.

Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:

- frequency and duration of contact,
- chemical resistance of glove material,
- glove thickness and
- dexterity

Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).

- When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.
- When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.
- Contaminated gloves should be replaced.

Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly.

Application of a non-perfumed moisturiser is recommended.

- Butyl rubber gloves.
- Nitrile rubber gloves.

OTHER

- Overalls.
- P.V.C. apron.
- Barrier cream.
- Skin cleansing cream.
- Eye wash unit.

RESPIRATOR

•Type AK-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

■ Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content. The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.

continued...

1098 HS Fount Solution

Hazard Alert Code: MODERATE

Chemwatch Material Safety Data Sheet

Issue Date: 10-Jul-2013

A317LP

CHEMWATCH 21-9552

Version No:3.1.1.1

Page 9 of 16

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required. For further information consult site specific CHEMWATCH data (if available), or your Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

■ Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.

Employers may need to use multiple types of controls to prevent employee overexposure.

Local exhaust ventilation usually required. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Supplied-air type respirator may be required in special circumstances. Correct fit is essential to ensure adequate protection.

An approved self contained breathing apparatus (SCBA) may be required in some situations.

Provide adequate ventilation in warehouse or closed storage area.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Water-white liquid with a characteristic odour; miscible with water.

PHYSICAL PROPERTIES

Liquid.

Mixes with water.

State	Liquid	Molecular Weight	Not Applicable
Melting Range (°C)	Not Available	Viscosity	Not Available
Boiling Range (°C)	100	Solubility in water (g/L)	Miscible
Flash Point (°C)	>61	pH (1% solution)	4.5- 4.7 (2%)
Decomposition Temp (°C)	Not Available	pH (as supplied)	Not Available
Autoignition Temp (°C)	Not Available	Vapour Pressure (kPa)	Negligible
Upper Explosive Limit (%)	Not Available	Specific Gravity (water=1)	1.05
Lower Explosive Limit (%)	Not Available	Relative Vapour Density (air=1)	Not Available
Volatile Component (%vol)	70%	Evaporation Rate	Not Available

Section 10 - STABILITY AND REACTIVITY

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

continued...

1098 HS Fount Solution

Hazard Alert Code: MODERATE

Chemwatch Material Safety Data Sheet

Issue Date: 10-Jul-2013

A317LP

CHEMWATCH 21-9552

Version No:3.1.1.1

Page 10 of 16

Section 10 - STABILITY AND REACTIVITY

For incompatible materials - refer to Section 7 - Handling and Storage.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

■ Accidental ingestion of the material may be damaging to the health of the individual.

Taken by mouth, isothiazolinones have moderate to high toxicity. The major signs of toxicity are severe stomach irritation, lethargy, and inco-ordination.

As absorption of phosphates from the bowel is poor, poisoning this way is less likely. Effects can include vomiting, tiredness, fever, diarrhoea, low blood pressure, slow pulse, cyanosis, spasms of the wrist, coma and severe body spasms.

Ingestion of ethanol (ethyl alcohol, "alcohol") may produce nausea, vomiting, bleeding from the digestive tract, abdominal pain, and diarrhoea. Effects on the body:

Blood concentration

<1.5 g/L

1.5- 3.0 g/L

3- 5 g/L

Effects

Mild: impaired vision, co- ordination and reaction time; emotional instability

Moderate: Slurred speech, confusion, inco-ordination, emotional instability, disturbances in perception and senses, possible blackouts, and impaired objective performance in standardized tests. Possible double vision, flushing, fast heart rate, sweating and incontinence. Slow breathing may occur rarely and fast breathing may develop in cases of metabolic acidosis, low blood sugar and low blood potassium. Central nervous system depression may progress to coma.

Severe: cold clammy skin, low body temperature and low blood pressure. Atrial fibrillation and heart block have been reported. Depression of breathing may occur, respiratory failure may follow serious poisoning, choking on vomit may result in lung inflammation and swelling. Convulsions due to severe low blood sugar may also occur. Acute liver inflammation may develop.

EYE

■ Solutions containing isothiazolinones may damage the mucous membranes and cornea. Animal testing showed very low concentrations (under 0.1%) did not cause irritation, while higher levels (3-5.5%) produced severe irritation and damage to the eye. Symptoms included clouding of the cornea and eye swelling.

There is evidence that material may produce eye irritation in some persons and produce eye damage 24 hours or more after instillation. Severe inflammation may be expected with pain. There may be damage to the cornea. Unless treatment is prompt and adequate there may be permanent loss of vision. Conjunctivitis can occur

continued...

1098 HS Fount Solution

Hazard Alert Code: MODERATE

Chemwatch Material Safety Data Sheet

Issue Date: 10-Jul-2013

A317LP

CHEMWATCH 21-9552

Version No:3.1.1.1

Page 11 of 16

Section 11 - TOXICOLOGICAL INFORMATION

following repeated exposure.

Direct contact of the eye with ethanol (alcohol) may cause an immediate stinging and burning sensation, with reflex closure of the lid, and a temporary, tearing injury to the cornea together with redness of the conjunctiva. Discomfort may last 2 days but usually the injury heals without treatment.

SKIN

■ Skin contact with the material may damage the health of the individual; systemic effects may result following absorption.

There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons.

Solutions of isothiazolinones may be irritating or even damaging to the skin, depending on concentration. A concentration of over 0.1% can irritate, and over 0.5% can cause severe irritation.

Open cuts, abraded or irritated skin should not be exposed to this material.

Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

INHALED

■ Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo.

There is some evidence to suggest that the material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.

Inhalation hazard is increased at higher temperatures.

Inhalation of high concentrations of gas/vapour causes lung irritation with coughing and nausea, central nervous depression with headache and dizziness, slowing of reflexes, fatigue and inco-ordination.

Inhalation of aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual.

Animal testing shows that the most common signs of inhalation overdose is inco-ordination and drowsiness.

CHRONIC HEALTH EFFECTS

■ Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population.

Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.

Sodium phosphate dibasic can cause stones in the kidney, loss of mineral from the bones and loss of thyroid gland function.

The isothiazolinones are known contact sensitizers. Sensitization is more likely with the chlorinated species as opposed to the non-chlorinated species. Risk of sensitization depends on how contact occurs – it is higher when the skin has been damaged. Skin specialist studies have shown sensitization has occurred with concentrations of 0.02% or less, and allergic reactions can occur in sensitized people with even lower concentrations. There is immune cross reaction between chlorinated isothiazolinones, but not between the non-chlorinated species or between non-chlorinated and chlorinated species. More experience is needed before conclusion of the safety of non-chlorinated species can be made.

There are conflicting reports in the literature, but isothiazolinones have been reported to cause mutations in certain bacteria. This effect has not been shown to occur in mammal cells. Animal testing showed no reproductive or tumour-inducing effects.

Repeated or prolonged exposure to corrosives may result in the erosion of teeth, inflammatory and ulcerative changes in the mouth and necrosis (rarely) of the jaw. Bronchial irritation, with cough, and frequent attacks of bronchial pneumonia may ensue. Gastrointestinal disturbances may also occur. Chronic exposures may result in dermatitis and/or conjunctivitis.

TOXICITY AND IRRITATION

■ unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

continued...

1098 HS Fount Solution

Hazard Alert Code: MODERATE

Chemwatch Material Safety Data Sheet

Issue Date: 10-Jul-2013

A317LP

CHEMWATCH 21-9552

Version No:3.1.1.1

Page 12 of 16

Section 11 - TOXICOLOGICAL INFORMATION

WATER:

5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE:

- No significant acute toxicological data identified in literature search.

5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE:

1098 HS FOUNT SOLUTION:

■ Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production.

■ The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons tested.

5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE:

SODIUM PHOSPHATE:

- The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.

D-GLUCOSE:

TOXICITY

Oral (rat) LD50:25800 mg/kg

Intraperitoneal (mouse) LD50:18000 mg/kg

Intravenous (mouse) LD50:9000 mg/kg

Specific development abnormalities reported in foetus include craniofacial, hepatobiliary, urogenital.

IRRITATION

Nil Reported

SODIUM PHOSPHATE:

TOXICITY

Oral (rat) LD50:17000 mg/kg

IRRITATION

Skin (rabbit):500 mg/24h - Mild

Eye (rabbit):500 mg/24h - Mild

for sodium phosphate, dibasic

5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE:

- The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

NOTE: Substance has been shown to be mutagenic in at least one assay, or belongs to a family of chemicals

continued...

1098 HS Fount Solution

Hazard Alert Code: MODERATE

Chemwatch Material Safety Data Sheet
Issue Date: 10-Jul-2013
A317LP

CHEMWATCH 21-9552
Version No:3.1.1.1
Page 13 of 16

Section 11 - TOXICOLOGICAL INFORMATION

producing damage or change to cellular DNA.
Considered to be the major sensitiser in Kathon CG (1)
(1). Bruze etal - Contact Dermatitis 20: 219-39, 1989

SKIN

D- glucose	GESAMP/EHS Composite List - GESAMP Hazard Profiles	D1: skin irritation/corrosion	0
------------	--	-------------------------------	---

Section 12 - ECOLOGICAL INFORMATION

5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE:
SODIUM PHOSPHATE:
DO NOT discharge into sewer or waterways.

D-GLUCOSE:
log Pow (Verschueren 1983): - 3.29
BOD5: 0.78
ThOD: 1.07
ThOD: 1.07
Degradation Biological: sig

SODIUM PHOSPHATE:

For Phosphate: The principal problems of phosphate contamination of the environment relates to eutrophication processes in lakes and ponds. Phosphorus is an essential plant nutrient and is usually the limiting nutrient for blue-green algae.

Aquatic Fate: Lakes overloaded with phosphates is the primary catalyst for the rapid growth of algae in surface waters. Planktonic algae cause turbidity and flotation films. Shore algae cause ugly muddying, films and damage to reeds. Decay of these algae causes oxygen depletion in the deep water and shallow water near the shore. The process is self-perpetuating because an anoxic condition at the sediment/water interface causes the release of more adsorbed phosphates from the sediment. The growth of algae produces undesirable effects on the treatment of water for drinking purposes, on fisheries, and on the use of lakes for recreational purposes.

Ecotoxicity:

Fish LC50 (48 h): Medaka, high eyes (*Oryzias latipes*): >10000 mg/l

5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE:

Marine Pollutant Yes

Very toxic to aquatic organisms.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

Environmental Fate: Isothiazolinones are antimicrobials used to control bacteria, fungi, and for wood preservation and antifouling agents. They are frequently used in personal care products such as shampoos and other hair care products, as well as certain paint formulations. The most common isothiazolinone combinations are 5-chloro-2-methyl-4-isothiazolin-3-one, (CMI), and 2-methyl-4-isothiazolin-3-one, (MI).

Aquatic Fate: 5-chloro-2-methyl-4-isothiazolin-3-one,(CMI), and 2-methyl-4-isothiazolin-3-one, (MI), undergo primary biological breakdown with half-lives of less than 24 hours in both oxygenated and low oxygen sediments with >55% breakdown occurring within 29 days.

Ecotoxicity: The isothiazolinones are very toxic to marine organisms, (fish, *Daphnia magna* water fleas, and algae), and have low potential for accumulation in aquatic species. The proposed metabolites of MI and CMI are considered to have a low aquatic toxicity, based partially on data for the structurally related N-(n-

continued...

1098 HS Fount Solution

Hazard Alert Code: MODERATE

Chemwatch Material Safety Data Sheet
Issue Date: 10-Jul-2013
A317LP

CHEMWATCH 21-9552
Version No:3.1.1.1
Page 14 of 16

Section 12 - ECOLOGICAL INFORMATION

octyl) malonamic acid.

Prevent, by any means available, spillage from entering drains or water courses.

Octanol/water Coefficient = 0.401 (log P)

Biodegradation (aquatic metabolism)

half life t1/2 anerobic = 4.8 hours

half life t1/2 aerobic = 17.3 hours

as mixed isothiazolinones

Rainbow trout LC50(96 hr) = 0.19 mg/L.

Bluegill Sunfish LC50(96hr) = 0.28 mg/L.

Daphnia EC50(48hr) = 0.16 mg/L.

Algal Selenastrum EC50: 0.018 mg/L.

Ecotoxicity

Ingredient	Persistence: Water/Soil	Persistence: Air	Bioaccumulation	Mobility
D- glucose	HIGH	No Data Available	LOW	HIGH
sodium phosphate	No Data Available	No Data Available	No Data Available	No Data Available
5- chloro- 2- methyl- 4- isothiazolin- 3- one	HIGH	No Data Available	LOW	HIGH

Section 13 - DISPOSAL CONSIDERATIONS

- Containers may still present a chemical hazard/ danger when empty.
- Return to supplier for reuse/ recycling if possible.

Otherwise:

- If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.

- Where possible retain label warnings and MSDS and observe all notices pertaining to the product.

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction
- Reuse
- Recycling
- Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.

- DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- Where in doubt contact the responsible authority.
- Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Authority for disposal.
- Bury or incinerate residue at an approved site.

continued...

1098 HS Fount Solution

Hazard Alert Code: MODERATE

Chemwatch Material Safety Data Sheet

Issue Date: 10-Jul-2013

A317LP

CHEMWATCH 21-9552

Version No:3.1.1.1

Page 15 of 16

Section 13 - DISPOSAL CONSIDERATIONS

- Recycle containers if possible, or dispose of in an authorised landfill.

Section 14 - TRANSPORTATION INFORMATION

HAZCHEM:

None (ADG7)

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS: ADG7, IATA, IMDG

Section 15 - REGULATORY INFORMATION

Indications of Danger:

Xn Harmful

POISONS SCHEDULE

None

REGULATIONS

Regulations for ingredients

D-glucose (CAS: 50-99-7, 492-62-6, 492-61-5, 5996-10-1) is found on the following regulatory lists;

"Acros Transport Information", "Australia Inventory of Chemical Substances (AICS)", "Australia Therapeutic Goods Administration (TGA) Substances that may be used as active ingredients in Listed medicines", "GESAMP/EHS Composite List - GESAMP Hazard Profiles", "IMO IBC Code Chapter 18: List of products to which the Code does not apply", "IMO MARPOL 73/78 (Annex II) - List of Other Liquid Substances", "International Fragrance Association (IFRA) Survey: Transparency List", "OECD List of High Production Volume (HPV) Chemicals", "Sigma-Aldrich Transport Information"

sodium phosphate (CAS: 7632-05-5) is found on the following regulatory lists;

"Australia Inventory of Chemical Substances (AICS)", "Australia National Pollutant Inventory", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix C", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix E (Part 2)", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix F (Part 3)", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 3", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 4", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6", "International Numbering System for Food Additives", "OECD List of High Production Volume (HPV) Chemicals"

5-chloro-2-methyl-4-isothiazolin-3-one (CAS: 26172-55-4) is found on the following regulatory lists;

"Australia - Victoria Occupational Health and Safety Regulations - Schedule 9: Materials at Major Hazard Facilities (And Their Threshold Quantity) Table 2", "Australia Inventory of Chemical Substances (AICS)", "Australia National Pollutant Inventory", "International Fragrance Association (IFRA) Survey: Transparency List", "OECD List of High Production Volume (HPV) Chemicals"

continued...

1098 HS Fount Solution

Hazard Alert Code: MODERATE

Chemwatch Material Safety Data Sheet

Issue Date: 10-Jul-2013

A317LP

CHEMWATCH 21-9552

Version No:3.1.1.1

Page 16 of 16

Section 15 - REGULATORY INFORMATION

water (CAS: 7732-18-5) is found on the following regulatory lists;

"Australia High Volume Industrial Chemical List (HVICL)", "Australia Inventory of Chemical Substances (AICS)", "IMO IBC Code Chapter 18: List of products to which the Code does not apply", "International Fragrance Association (IFRA) Survey: Transparency List", "OECD List of High Production Volume (HPV) Chemicals", "OSPAR National List of Candidates for Substitution – Norway", "Sigma-AldrichTransport Information"

No data for 1098 HS Fount Solution (CW: 21-9552)

Section 16 - OTHER INFORMATION

Denmark Advisory list for selfclassification of dangerous substances

Substance	CAS	Suggested codes
5- chloro- 2- methyl- 4- isothiazolin- 3- one	26172- 55- 4	R43

INGREDIENTS WITH MULTIPLE CAS NUMBERS

Ingredient Name	CAS
D-glucose	50-99-7, 492-62-6, 492-61-5, 5996-10-1

■ Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net/references.

■ The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: 10-Jul-2013

Print Date: 3-Apr-2014

This is the end of the MSDS.